



ELECTRIC WATER HEATER
 10 TO 15 L VERTICAL WALL MOUNTED
 ABOVE AND UNDER SINK
 30 TO 50 L SLIM VERTICAL WALL MOUNTED
 30 TO 50 L SLIM HORIZONTAL WALL MOUNTED
 COPPER HEATINGELEMENT

PREMIUM SMALL (Vertical wall mounted)

Technical data

Capacity (L)	Output (W)	Voltage (V)	Heat-up time at 60 °C (Δt=20 °C)	Heat-up time at 60 °C (Δt=50 °C)	Energy consumption (kWh/24h at 65 °C)
10 above sink	1600	230 (220/240)	10	24	0.48
15 above sink	2000	230 (230/240)	11	28	0.58
10 under sink	2000	230 (220/240)	8	19	0.63
15 under sink	2000	230 (220/240)	11	28	0.66

Dimensions

Capacity (L)	Dimensions (mm)						Flange opening (Ø mm)	Net weight (kg)
	H	Ø	B	C	D	E		
10 above sink	456	255	166	290	64	262	72	7.5
15 above sink	496	287	169	327	70	294	72	9.8
10 under sink	456	255	238	218	64	262	72	8
15 under sink	496	287	278	218	70	294	72	9



PREMIUM SLIM

Technical data (vertical wall mounted)

Capacity (L)	Output (W)	Voltage (V)	Heat-up time at 60 °C (Δt=50 °C)	Energy consumption (kWh/24h at 65 °C)
30	2000	230 (220/240)	57	0.76
50	2000	230 (220/240)	96	1.13

Technical data (horizontal wall mounted)

30	2000	230 (220/240)	0h57	0.88
50	2000	230 (220/240)	1h36	1.28
75	2000	230 (220/240)	2h07	1.55

Dimensions (vertical wall mounted)

Capacity (L)	Dimensions (mm)						Flange opening (Ø mm)	Net weight (kg)
	Ø	A	B	C	D	E		
30	338	623	160	463	81	345	72	12.5
50	338	918	168	750	81	345	72	17.2

Dimensions (horizontal wall mounted)

30	338	623	235	155	-	-	72	13.5
50	338	918	435	200	-	-	72	18.2
75	338	1190	-	-	-	-	72	22



Installation dimensions (in mm)

